



Straight line	Model Matio	50	60	80
	(mm)			
	min-max (W)	70-500	70-600	70-800
	min-max (L)	100-550	100-600	100-600
	min (a)	35	35	35
	(in)			
	min-max (W)	2.76-19.69	2.76-23.62	2.76-31.50
	min-max (L)	3.94-21.65	3.94-23.62	3.94-23.62
	min (a)	1.38	1.38	1.38

Dimensions depend on the equipment and the appropriate configuration of the machine

Double wall	Model Matio	50	60	80
	(mm)			
	min-max (W)	70-500	70-600	70-800
	min-max (L)	60-600	60-600	60-600
	min (e min)	10	10	10
	(in)			
	min-max (W)	2.76-19.69	2.76-23.62	2.76-31.50
	min-max (L)	2.36-23.62	2.36-23.62	2.36-23.62
	min (e min)	0.39	0.39	0.39

Dimensions depend on the equipment and the appropriate configuration of the machine

Model Matio	50	60	80
Processed materials			
Carton board max	800 g/m ³	800 g/m ³	800 g/m ³
Technical Data			
Voltage	400 V	400 V	400 V
Motor Power kW *	od 4 do 7	od 4 do 7	od 8-12
Length *	od 4 do 8	od 4 do 8	8,5-10,5
Net weight t *	od 4 do 6	od 4-6	od 4-7
Speed*	100m/min	100m/min	100m/min

* Parameters depend on the machine configuration

Model Matio	50	60	80
Processed materials			
Carton board max	800 g/m ³	800 g/m ³	800 g/m ³
Technical Data			
Voltage	400 V	400 V	400 V
Motor Power kW *	4 to 7	4 to 7	8 to 12
Length *	13.12 ft to 26.25 ft	13.12 ft to 26.25 ft	27.89 ft to 34.45 ft
Net weight t *	od 4 do 6	od 4-6	od 4-7
Speed*	328.08 ft/min	328.08 ft/min	328.08 ft/min

* Parameters depend on the machine configuration