




Straight line	Model Passio	55	80	115	145	165
	(mm)					
	min-max (W)	45*-550	45*-800	45*-1150	70-1450	70-1650
	min-max (L)	70-900	70-900	70-900	70-1000	70-1000
	min (a)	35	35	35	50	50
	(in)					
	min-max (W)	1.77*-21.65	1.77*-31.50	1.77*-45.28	2.76-57.09	2.76-64.96
	min-max (L)	2.76-35.43	2.76-35.43	2.76-35.43	2.76-39.37	2.76-39.37
min (a)	1.38	1.38	1.38	1.97	1.97	


Dimensions depend on the equipment and the appropriate configuration of the machine
* option

Double wall	Model Passio	55	80	115	145	165
	(mm)					
	min-max (W)	70-550	70-800	70-1000	70-1150	70-1150
	min-max (L)	60-800	60-800	60-800	60-1000	60-1000
	min (e min)	10	10	10	15	15
	(in)					
	min-max (W)	2.76-21.65	2.76-31.50	2.76-39.37	2.76-45.28	2.76-45.28
	min-max (L)	2.36-31.50	2.36-31.50	2.36-31.50	2.36-39.37	2.36-39.37
min (e min)	0.39	0.39	0.39	0.59	0.59	


Dimensions depend on the equipment and the appropriate configuration of the machine

Look bottom (k3 version required)	Model Passio	55	80	115	145	165
	(mm)					
	min-max (W)	100-550	100-800	100-1150	100-1450	100-1650
	min-max (L)	90-600	90-900	90-1000	90-1000	90-1000
	min (C)	70	70	70	70	70
	min (A)	20	20	20	20	20
	(in)					
	min-max (W)	3.94-21.65	3.94-31.50	3.94-45.28	3.94-57.09	3.94-64.96
min-max (L)	3.54-23.62	3.54-35.43	3.54-39.37	3.54-39.37	3.54-39.37	
min (C)	2.76	2.76	2.76	2.76	2.76	
min (A)	0.79	0.79	0.79	0.79	0.79	


Dimensions depend on the equipment and the appropriate configuration of the machine

Four corner (k4 version required)	Model Passio	55	80	115	145	165
	(mm)					
	min-max (W)	125-550	125-800	125-1150	147-1200	147-1200
	min-max (L)	120-800	120-800	120-1000	120-1000	120-1000
	min (d)	20	20	20	20	20
	min (C)	80	80	80	100	100
	(in)					
	min-max (W)	4.92-21.65	4.92-31.50	4.92-45.28	5.79-47.24	5.79-47.24
min-max (L)	4.72-31.50	4.72-31.50	4.72-39.37	4.72-39.37	4.72-39.37	
min (d)	0.79	0.79	0.79	0.79	0.79	
min (C)	3.15	3.15	3.15	3.94	3.94	

Dimensions depend on the equipment and the appropriate configuration of the machine

Four corner with lid (k4 version required)	Model Passio	55	80	115	145	165
	(mm)					
	min-max (W)	240-550	240-800	240-1150	260-1450	260-1650
	min-max (L)	120-800	120-1000	120-1000	120-1000	120-1000
	min (e)	90	90	90	90	90
	min (d)	20	20	20	20	20
	(in)					
	min-max (W)	9.45-21.65	9.45-31.50	9.45-45.28	10.24-57.09	10.24-64.96
min-max (L)	4.72-31.50	4.72-39.37	4.72-39.37	4.72-39.37	4.72-39.37	
min (e)	3.54	3.54	3.54	3.54	3.54	
min (d)	0.79	0.79	0.79	0.79	0.79	

Dimensions depend on the equipment and the appropriate configuration of the machine

Conical type (k3 version required)	Model Passio	55	80	115	145	165
	(mm)					
	min-max (W)	170-550	170-800	170-1150	170-1450	170-1650
	min-max (L)	70-800	70-800	70-900	70-900	70-900
	min (C)	75	75	75	90	90
	min (A)	20	20	20	20	20
	(in)					
	min-max (W)	6.69-21.65	6.69-31.50	6.69-45.28	6.69-57.09	6.69-64.96
min-max (L)	2.76-31.50	2.76-31.50	2.76-35.43	2.76-35.43	2.76-35.43	
min (C)	2.95	2.95	2.95	3.54	3.54	
min (A)	0.79	0.79	0.79	0.79	0.79	

Dimensions depend on the equipment and the appropriate configuration of the machine
* option

Model Passio	55	80	115	145	165
Processed materials					
Carton board max	800g/m ³	800g/m ³	800g/m ³	1000g/m ³	1000g/m ³
Corrugated flute type	A-N-F-E	N-F-E-B-A	N-F-E-B-A	A,B,C,E,F,N,BE,BF	A,B,C,E,F,N,BE,BF
Technical Data					
Voltage	400 V	400 V	400 V	400 V	400 V
Motor Power kW *	14-28	14-28	14-28	14-28	14-28
Length *	10-20 m	10-20 m	10-20 m	10-20 m	10-20 m
Net weight t *	od 8 do 11	od 10-15	od 10-15	od 10 do 16	od 10 do 17 t
Speed	200 m/min	200 m/min	200m/min	200 m/min	200m/min
Inching speed	do 400 m/min	do 400m/min	do 400m/min	do 300m/min	300 m/min

* Parameters depend on the machine configuration

Model Passio	55	80	115	145	165
Processed materials					
Carton board max	800 g/m ³	800 g/m ³	800 g/m ³	1000 g/m ³	1000 g/m ³
Corrugated flute type	A-N-F-E	N-F-E-B-A	N-F-E-B-A	A,B,C,E,F,N,BE,BF	A,B,C,E,F,N,BE,BF
Technical Data					
Voltage	400 V	400 V	400 V	400 V	400 V
Motor Power kW *	14-28	14-28	14-28	14-28	14-28
Length *	32.81-65.62 ft	32.81-65.62 ft	32.81-65.62 ft	32.81-65.62 ft	32.81-65.62 ft
Net weight t *	od 8 do 11	od 10-15	od 10-15	od 10 do 16	od 10 do 17 t
Speed	656.17 ft/min	656.17 ft/min	656.17 ft/min	656.17 ft/min	656.17 ft/min
Inching speed	to 1312.34 ft/min	to 1312.34 ft/min	to 1312.34 ft/min	to 984.25 ft/min	to 984.25 ft/min

* Parameters depend on the machine configuration